

CARUS[™] 1300 water treatment chemical is an effective sequestering agent developed specifically for use in potable and industrial water systems. The product is a liquid concentrate of exceptional purity, clarity, and stability. It is manufactured with the highest quality phosphates for sequestration.

BENEFITS OF CARUS™ 1300 WATER TREATMENT CHEMICAL

- · Controls iron and manganese, minimizing rusty or dirty water in the distribution system.
- Reduces discoloration, staining, and mineral buildup, resulting in fewer customer complaints.
- Diminishes calcium scale deposits typically seen in hot water lines and heaters.
- · Lowers chlorine consumption, which controls biofilm regrowth and improves disinfection in the distribution system.
- Decreases iron tuberculation, which can extend the life of the distribution system.
- Minimizes the occurrence of microbial-induced corrosion, providing longer system life. .

PROPERTIES AND CERTIFICATIONS

· Clear liquid

· Do not freeze

· Best if used within one year

• NSF Maximum Feed Rate: 32 mg/L

Specific Gravity: 1.33-1.39

pH: 7.4 ± 0.5

Weight: 11.0-11.6 lbs. per gallon

Conforms to ANSI/NSF Standard 60

SHIPPING AND HANDLING

CARUS[™] 1300 water treatment chemical is packaged and shipped in 30- and 55-, gallon containers and is also available in bulk quantities. The product is shipped in safety sealed polyethylene drums or certified tankers. Each container is identified by a lot number. Avoid contact with eyes, skin, and clothing. For complete information, please refer to the Material Safety Data Sheet (MSDS).

APPLICATION

CARUS[™] 1300 water treatment chemical is applied using a chemical metering pump. In most applications, the product is fed as a concentrate without the necessity of dilution. For dosage rates or answers to technical questions, please call Carus Phosphates, Inc. at (800) 929-6789.

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change; and the conditions of handling, use or misuse of the product are beyond our control. Carus Corporation makes no warranty, either express or implied, including any warranties of merchantability and fitness for a particular purpose. Carus also disclaims all liability for reliance on the completeness or confirming accuracy of any information included herein. Users should satisfy themselves that they are aware of all current data relevant to their particular uses.



CARUS PHOSPHATES INC.

181 Woodlawn Ave • Belmont, NC 28012 Tel: (704) 822-1441 Fax: (704) 822-0922 E-Mail: salesmkt@caruscorporation.com

Web: www.caruscorporation.com Copyright 2007

Form #PH Rev. 10/07